

Cold Water Gasoline Direct Drive

CA Aluminum Series

Fitted with our patented vibration isolation plate, the CA Series aluminum pressure washer is lightweight yet rugged.

Limited Warranties:

1 Year Mi-T-M Unloader **5 Year** Subaru Engine

3 Year Honda Engine **7 Year** Pump

3 Year Kohler Engine



CA-2703-1MMK

To see more online, scan here or go to www.mitm.com:



Pump

- ✓ Forged brass manifold
- ✓ Thermal relief valve
- ✓ In-line water strainer

Frame

- ✓ Patented vibration isolation plate
- ✓ Aluminum frame, base plate and handles

Unit Includes:

- ✓ 50-foot x 3/8-inch non-marking hose with quick connects
- ✓ Insulated trigger gun with safety lock-off

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CA-2403-1MMH	2400	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2403-1MMS	2400	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMH	2700	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMK	2700	2.4	208cc Kohler OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMS	2700	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-3003-1MAH	3000	3.0	270cc Honda OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAK	3000	3.0	277cc Kohler OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAS	3000	3.0	265cc Subaru OHC	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3504-1MAH	3500	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MAS	3500	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MGH*	3500	4.0	389cc Honda OHV	General	3-0350	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAH	4000	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAK	4000	3.5	429cc Kohler OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAS	4000	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MGH*	4000	4.0	389cc Honda OHV	General	3-0350	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.

*Model comes standard with external bypass system.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0097	External bypass system	2400 to 2700-PSI models
AW-8400-0021	Low pressure detergent injector	All models	CX-0098	External bypass system	3500 to 4000-PSI models except 1MGH
CX-0005	Insulated dual lance	All models	CX-0099	External bypass system	3000-PSI models