

Cold Water Gasoline Belt Drive

JCW Series

This rugged belt-driven unit is built with an all-steel frame and base plate. The JCW Series can handle even the toughest environments.

Limited Warranties:

- 1 Year** Mi-T-M Unloader
3500 & 4000-PSI models
- 5 Year** Subaru Engine
- 3 Year** Honda Engine
- 7 Year** Pump



JCW-4004-2MSB

Pump

- ✓ Forged brass manifold
- ✓ Thermal relief valve
- ✓ Water filter with clear sleeve for screen inspection

Frame

- ✓ Powder coated steel tube handles and base plate
- ✓ Two-piece belt guard with 1/4-turn release

Unit Includes:

- ✓ 50-foot x 3/8-inch non-marking hose with quick connects
- ✓ Insulated trigger gun with safety lock-off

To see more online, scan here or go to www.mitm.com:



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	MI-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JCW-2403-0MHB	2400	2.8	196cc Honda OHV	AR	3-0228	Adjustable pressure	0°, 15°, 25° & 40°	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2403-0MRB	2400	2.8	211cc Subaru OHC	AR	3-0228	Adjustable pressure	0°, 15°, 25° & 40°	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MHB	2700	2.4	196cc Honda OHV	AR	3-0228	Adjustable pressure	0°, 15°, 25° & 40°	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MRB	2700	2.4	211cc Subaru OHC	AR	3-0228	Adjustable pressure	0°, 15°, 25° & 40°	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-3504-2MHB	3500	3.7	389cc Honda OHV	AR	3-0308	Mi-T-M, adjustable pressure	0°, 15°, 25° & 40°	48in.	39.5x28.5x26in.	245 lb.	191 lb.
JCW-3504-2MSB	3500	3.7	404cc Subaru OHC	AR	3-0308	Mi-T-M, adjustable pressure	0°, 15°, 25° & 40°	48in.	39.5x28.5x26in.	245 lb.	191 lb.
JCW-4004-2MHB	4000	3.5	389cc Honda OHV	AR	3-0308	Mi-T-M, adjustable pressure	0°, 15°, 25° & 40°	48in.	39.5x28.5x26in.	249 lb.	195 lb.
JCW-4004-2MSB	4000	3.5	404cc Subaru OHC	AR	3-0308	Mi-T-M, adjustable pressure	0°, 15°, 25° & 40°	48in.	39.5x28.5x26in.	249 lb.	195 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0082	External bypass system - attaches to pump	3500 to 4000-PSI models
AW-8400-0021	Low pressure detergent injector	All models	CX-0085	External bypass system - attaches to base plate	3500 to 4000-PSI models
CX-0005	Insulated dual lance	All models			