

Semi-Trash Pumps - 2-Inch

Mi-T-M semi-trash pump is available with one of three engines: Honda OHV, Subaru OHC or Mi-T-M OHV. It features a 2-inch suction and discharge size that handle solids up to 3/4-inch and is ideal for civil engineering, construction and agricultural applications.

Limited Warranties:

- 1 Year** Mi-T-M Engine
- 2 Year** Pump
- 3 Year** Honda Engine
- 5 Year** Subaru Engine



WTP-S02-1MGM

Components

- ✓ Mechanical (silicon carbide) seal for longevity and performance
- ✓ Precision molded cast iron impeller and volute for reduced vibration and wear

To see more online, scan here or go to www.mitm.com:



MODEL NUMBER	SUCTION DISCHARGE SIZE	MAX. TOTAL HEAD	SUCTION LIFT	DISPLACEMENT/ENGINE	PSI	MAX. CAPACITY	FUEL TANK CAPACITY	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-S02-1MGH	2in.x2in.	115ft.	28ft.	118cc Honda OHV	50	9,720 gph	0.53 gal.	20.5x17x16.25in.	71 lb.	62 lb.
WTP-S02-1MGS	2in.x2in.	115ft.	28ft.	126cc Subaru OHC	50	9,720 gph	0.71 gal.	20.5x17x16.25in.	66 lb.	57 lb.
WTP-S02-1MGM	2in.x2in.	115ft.	28ft.	136cc Mi-T-M OHV	50	9,720 gph	0.71 gal.	20.5x17x16.25in.	72 lb.	63 lb.
WTP-S02-CMGM*	2in.x2in.	115ft.	28ft.	136cc Mi-T-M OHV	50	9,720 gph	0.71 gal.	20.5x17x16.25in.	72 lb.	63 lb.

*Model available in Canada only.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
15-0293	20-ft. x 2-in. hard suction hose with fittings	All models	19-0628	2-in. suction strainer	All models
15-0295	50-ft. x 2-in. soft discharge hose	All models	70-0524	2-in. suction and discharge kit	All models